



PACTOTop Primer

Epoxy based sealer & primer

DESCRIPTION

PACTOTop Primer is a high quality, epoxy sealer for porous surfaces and concrete. It is a ready to use product with excellent penetration properties and high resistance to abrasion and to chemicals. It is available in 2 grades: solvent based (SB) and solvent free (SF) suitable for close areas.

TYPICAL USES

PACTOTop Primer is recommended as primer to epoxy flooring system. It seals the porosity of the substrate and provides a compatible and adherent surface to finishing compounds or to screeds.

CHARACTERISTICS

Aspect: Two-component liquid
Color: Translucent (SB)
Clear (SF)

TECHNICAL CHARACTERISTICS

- Solid content by volume: 55 to 60%
- Specific gravity : 0.97 to 1.07

APPLICATION

- Theoretical spreading rate : 8 to 12 m²/ltr
- Thickness of dry film : 55 microns
- Thickness of wet film : 90 microns
- Dry time (30°C) : - Touch dry: 1-4 hrs
- Overcoat: 8-24 hrs
- Max. over-coating delay : 4 days
- Working pot life : 1-3 hours
- Application temp : +5 to + 40 deg C

INSTRUCTIONS FOR USE

Care should be taken to ensure surface is clean and free from grease, laitance and loose concrete. Mix the ready to use components in the same pre measured weights, using a slow speed drill machine fitted with a paddle. Mix both components for at least 3 minutes to obtain a uniform mix. Avoid part mixing.

Can be applied by brush, roller or conventional spray. For very porous surfaces two coats may be required to seal effectively.

THEORETICAL CONSUMPTION

The theoretical spreading rate is from 8 to 12 m²/liter (depending on substrate condition, porosity, texture and application methods.)

PACKAGING

PACTOTop Primer is supplied in 5, 6 & 20 liter pail.

SHELF LIFE

12 month from date of manufacturing in original unopened condition

STORAGE

PACTOTop Primer should be stored in a dry environment, away from direct sunlight or exposure to excess heat.

HEALTH AND SAFETY

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuff. Use goggles & gloves & suitable masks. Treat splashes to skin and eyes immediately by rinsing with clean water. If accidentally ingested, seek prompt medical attention. Reseal containers after use.

For more information please refer to MSDS, available on request.



P.O. Box no 282 676 Dubai-UAE
Tel: +971 4 885 0 886
Fax: +971 4 885 0 887
Visit us: www.pacttechnologies.ae

Important Note: Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, as the conditions of any labor involved in the application is beyond our control. PAC Technologies shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of this product. It is the responsibility of the user to ensure that the product meets his particular requirements and to use it in a suitable way. Field service, where provided, does not constitute supervisory responsibility. For additional Information contact your local PAC Technologies representative.