



PACTOFinish MRA-S

Solvent Based Chemical Release Agent

DESCRIPTION

PACTOFinish MRA-S is a chemically active mould release agent designed to provide clean and easy stripping of concrete formwork.

PRIMARY USES

PACTOFinish MRA-S is formulated for application to steel, timber and plastic faced formwork and moulds, prior to casting concrete, to ensure a clean release.

ADVANTAGES

- Quality surface finish does not stain.
- Ready to use by spray or roller application.
- Protects steel formwork from corrosion.
- Suitable for all types of formwork.
- May be applied immediately prior to casting earlier if required.
- Non slip
- Resistant to rain
- Produces high quality concrete surfaces ready to paint, coat or seal.
- Minimizes surface defects
- Economical

Action

PACTOFinish MRA-S reacts chemically with cement to impart excellent release properties to treated surfaces. Concrete cast against surfaces coated with **PACTOFinish MRA-S** exhibit a smooth, hard, uniform finish.

PACTOFinish MRA-S has no negative effect on the properties of concrete nor will it impair the adhesion of subsequent surface treatments when applied at the recommended coverage rates.

PACKAGING

200 liter drums. Bulk deliveries available upon request.

TYPICAL PROPERTIES

Properties listed are only for guidance and are guarantee of performance

| | |
|------------------|---------------------------|
| Component | : Single |
| Form | : Liquid |
| Colour | : Clear amber |
| Specific gravity | : 0.81 ± 0.05 at 25°C |

DIRECTION FOR USE

Apply before the first casting and thereafter re-apply immediately after stripping and cleaning the mould.

Lightweight horticultural sprayers are ideal as **PACTOFinish MRA-S** is finely atomized to give a uniform coating. Excessive application should be avoided.

Alternatively, application may be made by a fine haired brush, only a very thin coating should be made and any excess removed.

If after the first application, the **PACTOFinish MRA-S** is completely absorbed into new timber or plywood, a further application should be made before filling the moulds of formwork.

COVERAGE

The coverage rate for **PACTOFinish MRA-S** is 30 to 50 m²/liter/coat when spray applied depending on smoothness and porosity of the formwork used.

Note

Progressively better results are obtained on plywood and timber moulds as they become impregnated and the operatives become accustomed to working with the release agent.



PACTOFinish MRA-S in general, may be used over timber moulds.etc. , which have been treated with other moulds oils, providing excess has been removed.

EQUIPMENT CARE

PACTOFinish MRA-S may usually be left in spray guns or sprayers without detriment, but with certain types, there may be some softening of rubber seals with prolonged contact.

STORAGE AND SHELF LIFE

Store under cover, out of direct sunlight and protect from extremes of temperature. Storage life up to 12 months when stored in unopened containers as above.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult PAC Technologies Technical Services Department.

HEALTH AND SAFETY

As with all chemical products. Care should be taken during use and storage to avoid contact with eyes mouth. Skin and foodstuffs (which can also be tainted with vapor until product fully cured or dried). Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Keep away from children and animals. Reseal containers after use.



P.O. Box no 282 676 Dubai-UAE
Tel: +971 4 885 0 886
Fax: +971 4 885 0 887
Visit us: www.pactechnologies.ae

Important Note: Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, as the conditions of any labor involved in the application is beyond our control. PAC Technologies shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of this product. It is the responsibility of the user to ensure that the product meets his particular requirements and to use it in a suitable way. Field service, where provided, does not constitute supervisory responsibility. For additional Information contact your local PAC Technologies representative.

October 2011

Page 2 of 2