



DESCRIPTION

PACTOFinish R is a liquid surface retarder for concrete to provide exposed aggregate finish and for obtaining a mechanical key for construction joints.

PRIMARY USES

PACTOFinish R is used to achieve exposed aggregate surfaces for decorative and architectural coloured & normal concrete. Excellent in providing key for joint between old concrete and new concrete. It can be used on face down condition. Used for precast panels, construction joints, renders, screeds, paving, slabs, etc.

ADVANTAGES

- A uniform depth of retardation is achieved
- Economical and simple method for exposed surface finishes
- Treated surfaces give excellent bond for renders and concrete saving costly scabbling
- Does not reduce concrete strength

TECHNICAL DATA (TYPICAL PROPERTIES at 25°C)

PROPERTY	TEST METHOD	VALUE
Component		Single
Form		Liquid
Colour		Slight Yellow
Specific Gravity	ASTM D1475	1.07 +/- 0.02
Surface Retardation		3-5 mm (depends on application rate and concrete mix design)

APPLICATION

PACTOFinish R is a ready to use liquid. It should not be diluted. **PACTOFinish R** should be applied to concrete surfaces immediately after finishing. It can be applied on shutters in face down direction. Concrete should be poured immediately on such surfaces. The concrete should be proportioned to minimise segregation and bleeding. Once the concrete has hardened sufficiently the shutter/moulds can be removed. The depth of retarded portion of the concrete matrix can be easily removed by wire brush or water jet washing to expose the aggregate.

PACKAGING

5 ltr, 20 ltr and 200 ltr

COVERAGE

7-10 m²/ltr/coat (coverage depends on surface finish, porosity and texture)

STORAGE AND SHELF LIFE

Shelf Life 12 months from date of manufacture when stored under warehouse conditions in original unopened packing.

Extreme temperature/humidity may reduce shelf life.

EQUIPMENT CLEANING

Clean all equipments and tools with PAC Cleaner immediately after use.

HEALTH AND SAFETY

PPE's Gloves, goggles and suitable mask must be worn. Precautions: Contact with skin, eyes, etc. must be avoided. If swallowed seek medical attention immediately. Hazard: Regarded as non-hazardous for transportation. Disposal : Do not reuse containers. To be disposed off as per local rules and regulations. Additional Information Refer MSDS. Available on request.



P.O. Box no 282 676 Dubai-UAE
Tel: +971 4 885 0 886
Fax: +971 4 885 0 887
Visit us: www.pactechnologies.ae

Important Note: Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, as the conditions of any labor involved in the application is beyond our control. PAC Technologies shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of this product. It is the responsibility of the user to ensure that the product meets his particular requirements and to use it in a suitable way. Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local PAC Technologies representative.