

DESCRIPTION

PACTORep LRR is a single component, liquid applied, rust removing compound based on chloride free special chemicals for steel surfaces.

PRIMARY USES

PACTORep LRR is used to remove rust from steel surfaces, concrete reinforcement steel rebars before concreting and repairs, steel structures like tanks, pipelines, columns, beams, trusses, etc. before painting, steel column base plate and machine base plate before grouting, etc

ADVANTAGES

- Easy to apply, low labour cost
- Free of corrosion causing chlorides
- Effective rust removal even from difficult access areas
- Reduces down time for painting, concreting or repairs
- Does not affect concrete adversely

TECHNICAL DATA (TYPICAL PROPERTIES at 25°C)

PROPERTY	TEST METHOD	VALUE
Component	-	Single
Form	-	Liquid
Colour	-	Translucent
Specific Gravity	ASTM D1475	1.30 +/- 0.05
pH	ASTM C494	2.5 +/- 0.05

APPLICATION INSTRUCTION

Surface Preparation

Heavily rusted steel surfaces should be wire brushed to remove the loose rust and scale. Removing of scales with other mechanical means like hammering, grinding, etc. also should be considered. This will help in enhancing the speed and performance of rust removal.

APPLICATION

Agitate the container to stir the contents well. Apply **PACTORep LRR** evenly on prepared surface by brush, sponge, spray, roller, etc. till the substrate gets saturated. Leave the applied surface for 20 to 30 minutes for complete reaction. Then wipe clean the steel surface to remove the loose rust particles. Treated area should be water jetted before proceeding for new concrete, placing of repair mortar or painting. Ensure that all traces of rust remover washed off the surface of concrete and steel dilution: Though **PACTORep LRR** is a ready to use product, it can be diluted with water in the proportion of 1:1 to 1:4 depending on intensity of the rust. Exact proportion of dilution should be determined by site trials.

PACKAGING

20 ltr. and 200 ltr.

COVERAGE

5 to 20 m² / ltr

Coverage depend on substrate and intensity of rust.

STORAGE AND SHELF LIFE

Shelf Life 12 months from date of manufacture when stored under warehouse conditions in original unopened packing. Extreme temperature/humidity may reduce shelf life.

EQUIPMENT CLEANING

Clean all equipments and tools with PAC Cleaner immediately after use.

HEALTH AND SAFETY

PPE's Gloves, goggles and suitable mask must be worn. Precautions: Contact with skin, eyes, etc. must be avoided. If swallowed seek medical attention immediately. Hazard: Regarded as non-hazardous for transportation. Disposal: Do not reuse containers. To be disposed off as per local rules and regulations. For additional Information please refer to the MSDS available on request.



P.O. Box no 282 676 Dubai-UAE
Tel: +971 4 885 0 886
Fax: +971 4 885 0 887
Visit us: www.pactechnologies.ae

Important Note: Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, as the conditions of any labor involved in the application is beyond our control. PAC Technologies shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of this product. It is the responsibility of the user to ensure that the product meets his particular requirements and to use it in a suitable way. Field service, where provided, does not constitute supervisory responsibility. For additional Information contact your local PAC Technologies representative.