



DESCRIPTION

PACTOProof BM-S is a specially formulated solvent based bituminous primer. It improves the adhesion of bituminous products to concrete surfaces.

It is designed to be brush or spray application to provide an economic continuous layer of primer.

TYPICAL USES

- As a primer for the torch applied and self adhesive Bituminous membranes.

TECHNICAL DATA

Complies with ASTM D-41 Type II

Tests

As supplied

	<u>Requirement</u>
Water, volume %	0.5% max.
Saybolt Furol Viscosity,(25 °C)	25-125 S
Distillation, volume of primer	
To 225 °C	30% min.
To 360 °C	60% max.

Residue to 360 °C

Penetration, 25 °C	20 to 50
Solubility	99% min

Drying time 1- 3 hour

Specific Gravity	0.88
Service temperature	0 – 70 °C

Application rate

Apply at a rate of 4-6 m²per liter depending on the texture and porosity of the substrate..

Application

- Temperature during application shouldn't be less than 7 °C
- Shouldn't be applied in rain
- Could be applied by roller, brush or spray

PACKAGING

Supplied in 15 ltr. tin and 200 ltr. drum

STORAGE AND SHELF LIFE

PACTOProof BM-S has a shelf life of 12 months when stored away from direct sunlight, between 5°C and 45°C in the original sealed containers.

HEALTH AND SAFETY

There are no known health hazards associated with PACTOProof BM-S in normal use.

Harmful by inhalation of vapour.

Wear gloves and eye protection.

Keep away from flame and do not smoke.



P.O. Box no 282 676 Dubai-UAE

Tel: +971 4 885 0 886

Fax: +971 4 885 0 887

Visit us: www.pactechnologies.ae

Important Note: Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, as the conditions of any labor involved in the application is beyond our control. PAC Technologies shall not be liable for any injury, loss or damage, direct or consequential, arising out of the use of this product. It is the responsibility of the user to ensure that the product meets his particular requirements and to use it in a suitable way. Field service, where provided, does not constitute supervisory responsibility. For additional Information contact your local PAC Technologies representative.

